



PORTABLE VIDEO INSPECTION SYSTEM

This feature can greatly expand the applications for Vac-Con combination sewer cleaners. Examples: broken pipes, protruding laterals, off grade pipes, offset joints, leaking joints, recessed taps, cracked pipes, blockages, corrosion, grease build up, root infiltration, collapsed pipes, clean outs, drain lines, service laterals vent stacks, floor drains, water lines, internal plumbing system, utility ducts, etc.

- High definition LCD color monitor .
- Mounted on a pivot style assembly enabling operator to adjust to different applications.
- Monitor spec's 6.5" high x 8.5" wide. 12VDC or 110VAC power operation.
- Sun shield for light deflection.
- Self leveling Camera head is propelled by the high pressure water system & hose on the combination sewer cleaner. The camera head has preset aperture settings of $f1.8$, a 100° angle 2.5mm lens. 21 high brightness white LED cluster lights provide 160° angle of illumination w/variable settings. Camera housing is HD aluminum & factory sealed. Camera lens is a high impact sapphire window.
- Camera skids 6", 8" & 10" are standard.
- High pressure hose reel mounted video cable reel with capacity of 600'. Mounted on a pivot assembly to enable operator to pivot the camera reel into the camera operation position or the non-camera operation position. The video reel is hydraulically operated in sequence with the sewer hose reel.
- Flash board drive (DVR) digital video recorder with scan disc reader



- Folding keyboard, on screen digital footage
- Optional: Manually operated push cable reel assembly with 150 ft. of cable, shall also be provided for remote applications.
- Skids up to 12"

FIRST IN INNOVATION !